



AirPlus XTREME G™

High-Speed 2.4GHz Wireless Router



Home

Advanced

Tools

Status

Help

Wizard

Wireless

WAN

LAN

DHCP

WAN Settings

Please select the appropriate option to connect to your ISP.

- Dynamic IP Address Choose this option to obtain an IP address automatically from your ISP. (For most Cable modem users)
- Static IP Address Choose this option to set static IP information provided to you by your ISP.
- PPPoE Choose this option if your ISP uses PPPoE. (For most DSL users)
- Others
 - PPTP (for Europe use only)
 - BigPond Cable (for Australia use only)

Dynamic IP

Host Name (optional)

MAC Address - - - - -
 (optional) Clone MAC Address


Primary DNS Address

Secondary DNS Address (optional)


MTU




 Apply Cancel Help




D-Link
Building Networks for People



AirPlus Xtreme G™
High-Speed 2.4GHz Wireless Router

Home
Advanced
Tools
Status
Help



DI-624

Admin

Time

System

Firmware

Misc.

Ping Test
Ping Test is used to send "Ping" packets to test if a computer is on the Internet.

Host Name or IP address

Restart Device
Reboots the DI-624.

Block WAN Ping

When you "Block WAN Ping", you are causing the public WAN IP address on the DI-624 to not respond to ping commands. Pinging public WAN IP addresses is a common method used by hackers to test whether your WAN IP address is valid.

Discard PING from WAN side Enabled Disabled

UPNP Settings

Enabled Disabled

Gaming Mode

Enabled Disabled

VPN Pass-Through
Allows VPN connections to work through the DI-624.

PPTP Enabled Disabled

IPSec Enabled Disabled

Dynamic DNS

DDNS Enabled Disabled

Server Address

Host Name

Username

Password

Apply Cancel Help



DI-624

Virtual Server

Applications

Filters

Firewall

DMZ

Performance

Home **Advanced** Tools Status Help

Wireless Performance

These are the Wireless Performance features for the AP(Access Point) Portion.

- TX Rate : (Mbps)
- Beacon interval : (msec, range:20~1000, default:100)
- RTS Threshold : (range: 256~2432, default:2432)
- Fragmentation : (range: 256~2346, default:2346, even number only)
- DTIM interval : (range: 1~255, default:1)
- Preamble Type : Short Preamble Long Preamble
- Authentication : Open System Shared Key
- SSID Broadcast : Enabled Disabled
- 802.11g Only Mode : Enabled Disabled
- Frame Burst :

Apply Cancel Help



DI-624

Virtual Server

Applications

Filters

Firewall

DMZ

Performance

Home **Advanced** Tools Status Help

Firewall Rules

Firewall Rules can be used to allow or deny traffic from passing through the DI-624.

Enabled Disabled

Name

Action Allow Deny

Interface	IP Range Start	IP Range End	Protocol	Port Range
Source	*			
Destination	*		TCP	-

Schedule Always

From time 00 : 00 AM to 00 : 00 AM
day Sun to Sun

Apply Cancel Help

Firewall Rules List

ActionName	Source	Destination	Protocol
<input checked="" type="checkbox"/> Allow BitTorrent	WAN,*	LAN,192.168.71.32	TCP,6881-6999
<input checked="" type="checkbox"/> Deny	LAN,67.113.225.68	WAN,*	TCP,80
<input checked="" type="checkbox"/> Allow Virtual Server FTP	WAN,*	LAN,192.168.71.9	TCP,21
<input checked="" type="checkbox"/> Allow Virtual Server HTTP	WAN,*	LAN,192.168.71.9	TCP,80
<input checked="" type="checkbox"/> Allow Virtual Server HTTPS	WAN,*	LAN,192.168.71.9	TCP,443
<input checked="" type="checkbox"/> Allow Virtual Server SSH	WAN,*	LAN,192.168.71.9	TCP,22
<input checked="" type="checkbox"/> Allow VNC	WAN,*	LAN,192.168.71.32	TCP,5900
<input checked="" type="checkbox"/> Allow ReplayTV IVS	WAN,*	LAN,192.168.71.200	TCP,5040
<input checked="" type="checkbox"/> Allow BitTorrentTrackerHTTP	WAN,*	LAN,192.168.71.32	TCP,6969
<input checked="" type="checkbox"/> Allow Gnutella	WAN,*	LAN,192.168.71.32	IP (0),6346
<input checked="" type="checkbox"/> Allow DirectConnectTCP	WAN,*	LAN,192.168.71.32	IP (0),1412
<input checked="" type="checkbox"/> Allow BitTorrent	WAN,*	LAN,192.168.71.32	IP (0),34457
<input checked="" type="checkbox"/> Deny Default	*,*	LAN,*	IP (0),*
<input checked="" type="checkbox"/> Allow Default	LAN,*	*,*	IP (0),*



Virtual Server

Applications

Filters

Firewall

DMZ

Performance

Home

Advanced

Tools

Status

Help

Special Application

Special Application is used to run applications that require multiple connections.

Enabled Disabled

Name [input] Clear

Trigger Port [input] - [input]

Trigger Type TCP

Public Port [input]

Public Type TCP

Special Applications List

Apply Cancel Help

NAME	Trigger	Public	
<input type="checkbox"/> Battle.net	6112	6112	
<input type="checkbox"/> Dialpad	7175	51200-51201,51210	
<input type="checkbox"/> ICU II	2019	2000-2038,2050-2051,2069,2085,3010-3030	
<input type="checkbox"/> MSN Gaming Zone	47624	2300-2400,28800-29000	
<input type="checkbox"/> PC-to-Phone	12053	12120,12122,24150-24220	
<input type="checkbox"/> Quick Time 4	554	6970-6999	



- DI-624
-
- Virtual Server
- Applications
- Filters
- Firewall
- DMZ
- Performance

- Home
- Advanced
- Tools
- Status
- Help

Virtual Server

Virtual Server is used to allow Internet users access to LAN services.

Enabled Disabled

Name

Private IP

Protocol Type

Private Port

Public Port

Schedule Always

From time : AM to : AM day to

Apply Cancel Help

Virtual Servers List

Name	Private IP	Protocol	Schedule	
<input checked="" type="checkbox"/> Virtual Server FTP	192.168.71.9	TCP 21/21	always	
<input checked="" type="checkbox"/> Virtual Server HTTP	192.168.71.9	TCP 80/80	always	
<input checked="" type="checkbox"/> Virtual Server HTTPS	192.168.71.9	TCP 443/443	always	
<input type="checkbox"/> Virtual Server DNS	0.0.0.0	UDP 53/53	always	
<input type="checkbox"/> Virtual Server SMTP	0.0.0.0	TCP 25/25	always	
<input type="checkbox"/> Virtual Server POP3	0.0.0.0	TCP 110/110	always	
<input type="checkbox"/> Virtual Server Telnet	0.0.0.0	TCP 23/23	always	
<input type="checkbox"/> IPsec	0.0.0.0	UDP 500/500	always	
<input type="checkbox"/> PPTP	0.0.0.0	TCP 1723/1723	always	
<input type="checkbox"/> NetMeeting	0.0.0.0	TCP 1720/1720	always	
<input checked="" type="checkbox"/> Virtual Server SSH	192.168.71.9	TCP 22/22	always	
<input checked="" type="checkbox"/> VNC	192.168.71.32	TCP 5900/5900	always	
<input checked="" type="checkbox"/> Gnutella	192.168.71.32	IP (0) 6346/6346	always	
<input checked="" type="checkbox"/> DirectConnectTCP	192.168.71.32	IP (0) 1412/1412	always	
<input checked="" type="checkbox"/> ReplayTV IVS	192.168.71.200	TCP 5040/5040	always	
<input checked="" type="checkbox"/> BitTorrentTrackerHTTP	192.168.71.32	TCP 6969/6969	always	
<input checked="" type="checkbox"/> BitTorrent	192.168.71.32	IP (0) 34457/34457	always	

DI-624



Wizard

Wireless

WAN

LAN

DHCP

Home

Advanced

Tools

Status

Help

DHCP Server

The DI-624 can be setup as a DHCP Server to distribute IP addresses to the LAN network.

 DHCP Server Enabled Disabled

 Starting IP Address 192 . 168 . 71 .

 Ending IP Address 192 . 168 . 71 .

 Lease Time
Static DHCP

Static DHCP is used to allow DHCP server to assign same IP to specific MAC address.

 Enabled Disabled

 Name

 IP 192 . 168 . 71 .

 MAC Address - - - - -

 DHCP Client


Apply



Cancel



Help

Static DHCP Client List

Host Name	IP Address	MAC Address
vault	192.168.71.9	00-E0-18-23-11-D0
RTV Family Room	192.168.71.200	00-0A-97-01-D9-67
NewEMMA	192.168.71.11	00-01-03-23-C5-EC
VIDRIGX	192.168.71.10	00-07-E9-7B-87-0C
moab	192.168.71.32	00-04-61-58-1E-83
NewEMMA	192.168.71.100	00-0D-88-7F-E9-76

Dynamic DHCP Client List

Host Name	IP Address	MAC Address	Expired Time
-----------	------------	-------------	--------------



DI-624



Device Info

Log

Stats

Wireless

Home

Advanced

Tools

Status

Help

Device Information

Firmware Version: 1.24 , Wed, 23 Jul 2003

LAN

MAC Address 00-40-05-5E-E4-E5

IP Address 192.168.71.1

Subnet Mask 255.255.255.0

DHCP Server Enabled

WAN

MAC Address 00-03-6D-13-81-DD

Connection DHCP Client Connected

IP Address 64.53.242.2

Subnet Mask 255.255.255.128

Default Gateway 64.53.242.1

DNS 64.233.207.2 64.233.207.16

Wireless 802.11g

MAC Address 00-80-C8-2B-72-1B

SSID oldskool

Channel 6

WEP 128 bits



Help