

Formatted Capacity.....	106.9 MB
Number of Cylinders.....	1024
Number of Heads.....	12
Head Landing Zone.....	0
Number of Sectors per Track.....	17
Recording Method.....	RLL (2,7) ZBR
Transfer Rate Internal.....	up to 15 mbits/sec
Average Access Time.....	sub 15 ms
Track-to-Track Access Time.....	3 ms
Rotation Speed.....	3211 rpm
Head Parking.....	Automatic
Onboard Cache.....	32 K
Manufacturer.....	Seagate
Model Number.....	ST-3120A
Interface.....	AT
MTBF.....	150,000 hrs
Temperature:	
Operating.....	41° to 131°F (5° to 55°C)
Non-Operating.....	-40° to 158°F (-40° to 70°C)
Humidity:	
Operating.....	8% to 80% RH non-condensing
Non-Operating.....	5% to 95% RH non-condensing
Maximum Wet Bulb.....	79°F (29°C)
Power Requirements:	
Startup.....	+12V 0.9 amps
Active.....	5.3 watts
Idle.....	2.1 watts
Standby.....	0.7 watts
Physical:	
Height.....	1.0 inch
Width.....	4.02 inch
Depth.....	5.77 inch
Weight.....	1.3 lbs

The hard drive is normally configured as type "AUTO" in the setup utility.

(rjs-07/08/93)