

KX-P3200 High Speed Forms Printer



Features:

- Easy-access bottom push tractor
- Straight paper path
- Accommodates up to 5-part forms
- High speed printing: maximum 330 cps
- Long life ribbon of approximately 6 million characters
- Parallel & Serial Interfaces
- Setup disk includes Windows™ 95, 3.11 and 3.1 Printer Drivers

All product/brand names are trademarks or registered trademarks of their respective holders. Specifications subject to change without notice. Product may be subject to export control regulations. Copyright © 1997 Matsushita Electric Corporation of America. All rights reserved.

O n l i n e S p e c S h e e t



Panasonic Computer Peripheral Company
Division of Panasonic Communications & Systems Company
Unit of Matsushita Electric Corporation of America
Imaging Products Group
Headquarters: 2 Panasonic Way, Secaucus, NJ 07094

www.panasonic.com/alive

KX-P3200 Specifications

Print Method	Impact Serial Dot Matrix		
Printhead and Life	(0.3 mm wire diameter), 200 mil strokes; 100 mil chr (draft)		
Print Direction	Text: Bi-directional (user selectable unidirectional) logic seeking; Graphics: Unidirectional		
Character Matrix	Draft (9x9), NLQ (18x18), HSD (8x9)		
Print Speed		Draft	NLQ HSD
	15 cpi Micron	330 cps	44 cps -
	12 cpi Elite	264 cps	53 cps 317 cps
	10 cpi Pica	220 cps	44 cps 264 cps
Printing Sizes	5,6,7.5,8.5,10,12,15,17,20 cps, &PS		
Characters Per Line	40, 48, 60, 68, 80, 96, 120, 137 & 160 cpl		
Lines Per Inch	6 , 8, 7/72, n/72, n/216 & programmable lpi		
Character Sets	Epson mode: 1 Italic & 17 character set tables 15 International characters and Legal Set, IBM mode: 17 character set tables		
Bit Image (matrix)	240 x 216 dots per inch		
Line Feed Time	Approx. 90 msec. (with 1/6 inch line feeding)		
Setup Disk	3-1/2" disk controls all printer functions, Includes a command reference program and drivers for Windows™ 95, 3.11 & 3.1.		
Tractor Feed	Push		
Paper Feed Path	Bottom		
Paper Specifications	Continuous 4.0 to 10.0 inches, 16 to 24 lbs.		
Copies	Up to original +4 non-carbon copies		
Thickness	Maximum thickness 0.014 in.		
Emulations	Epson FX-850, IBM Proprinter III		
Interfaces	Centronics parallel & RS-232C/serial		
Buffer	12K (standard), additional 32K (optional)		
Noise Level	<55 dBA		
Environment	Operating: 50°F to 95°F, 20 to 80% humidity Storage: -4°F to 140°F, 10 to 90% humidity		
Reliability	5000 hrs MTBF @ 25% duty cycle		
Dimensions & Weight	16.8" (w) x 8.5" (d) x 7.8" (h); 10.8 lbs.		
Power Consumption	Standby 10W; maximum 90W		
Warranty	2 Year Express Exchange Warranty See your dealer for details.		
Options & Accessories	KX-P44 32K Buffer Chip, KX-P180 Endless black fabric ribbon cassette, Life expectancy approx. 6 million charac. (in draft mode/rolling ASCII)		