

TECRA SERIES SPECIFICATIONS

FEATURES	Tecra 710CDT	Tecra 720CDT
PROCESSOR (Intel)	133MHz Pentium w/co-processor	133MHz Pentium w/co-processor
PROCESSOR TYPE	Pentium (2.9v/3.3v w/16KB cache)	Pentium (2.9v/3.3v w/16KB cache)
RAM	16 MB EDO EXP. 144 MB (60ns)	16 MB EDO EXP. 144 MB (60ns)
L2 RAM CACHE	256KB SRAM (14ns)	256KB SRAM (14ns)
DISPLAY SIZE	12.1" (9.68"W x 7.26"H)	12.1" (9.68"W x 7.26"H)
DISPLAY TYPE	TFT-LCD Active Matrix Color	TFT-LCD Active Matrix Color
Video Memory	2 MB - PCI video bus w/burst mode	2 MB - PCI video bus w/burst mode
Video Chip Set	C&T HIQV32 (CT65550)	C&T HIQV32 (CT65550)
INTERNAL COLOR	800 x 600/16.7M of 16.7M colors	1024 x 768/64K of 64K colors
EXTERNAL COLOR	<u>Colors/Palette</u>	<u>Colors/Palette</u>
	640 x 480 16.7M colors/ 16.7M colors	16.7M colors/ 16.7M colors
	800 x 600 16.7M colors/ 16.7M colors	16.7M colors/ 16.7M colors
	1024 x 768 64K colors/ 64K colors	64K colors/ 64K colors
	1280 x 1024 256 colors/ 256K colors	256 colors/ 256K colors
FDD	Included/Swappable with CD	Included/Swappable with CD
2nd Battley Support	Not Available	Not Available
MODULAR HDD	Not Available	Not Available
INTERNAL CD-ROM	(6X) Installed/Swappable with FDD	(6X) Installed/Swappable with FDD
HDD (2.5" IDE)	Removeable 1.13GB (13 msec)	Removeable 1.13GB (13 msec)
EXPANSION TYPE	1- Stacked PC Card Slot ♣	1- Stacked PC CardBusSlot ♣
Internal Sound Slot	Installed:16bit stereo full-duplex ♦	Installed:16bit stereo full-duplex ♦
Internal Modem	Installed: 28.8 Kbps Data/Fax/ Voice	Installed: 28.8 Kbps Data/Fax/ Voice
Dockability	Optional DS V Plus orNotedock II	Optional DS V Plus orNotedock II
PORTS	1 Serial (16550 UART equiv.)	1 Serial (16550 UART equiv.)
Serial Infrared port	1 IrDA 115.2Kbps compatible	1 IrDA 115.2Kbps compatible
Parallel port	1 Parallel: ECP	1 Parallel: ECP
SVGA port	1 RGB	1 RGB
PS/2 Mouse port	Combined with Keyboard port	Combined with Keyboard port
PS/2 Keyboard Port	1 101-key keyboard port	1 101-key keyboard port
Pointing Device	Accupoint Integrated Mouse	Accupoint Integrated Mouse
ZV port enabled	Yes	Yes
FDD port	1 FDD Port	1 FDD Port
AC POWER UNIT	External	External
BATTERY	LITHIUM ION (10.8V, 5600mAH)	LITHIUM ION (10.8V, 5600mAH)
BATTERY LIFE	4 HRS. (MAX)	4 HRS. (MAX)
BAT. RECHARGE	4HRS (OFF)/4.5-10.5 HRS (ON)	4HRS (OFF)/4.5-10.5 HRS (ON)
DIMENSIONS	11.8" x 9.1" x 2.3"	11.8" x 9.1" x 2.3"
TOTAL WEIGHT	< 8.0 lbs. (includes Battery: 1.32 lbs.)	< 8.0 lbs. (includes Battery: 1.32 lbs.)
WARRANTY	3 YR. Parts & Labor	3 YR. Parts & Labor

♣ NOTE: The Stacked PC card slot holds (2) 5mm PC cards Type II or (1) 10.5mm PC card Type III. CardBus slots are 32-bit 3.3V also compatible with 16-bit 5V PC Card standar

♦ Crystal Semiconductor sound card support Soundblaster Prø™, .WAV, and MIDI files.